

UL-Listed Couplings Selection Table

H.P.	3500	2900	1750	1450	H.P.	
7 1/2	ROTEX 42	ROTEX 42	ROTEX 42	ROTEX 42	7 1/2	
10					10	
15					15	
20					20	
25			25			
30			30			
40			ROTEX 55	ROTEX 55	ROTEX 55	40
50						50
60			ROTEX 65	ROTEX 65	ROTEX 65	60
75						75
100	ROTEX 55	ROTEX 55	ROTEX 75	ROTEX 75	100	
125	ROTEX 65	ROTEX 65			125	
150	C1060T	C1060T	ROTEX 90	ROTEX 90	150	
200					200	
250			C1080T	C1080T	250	
300					300	
350	N/A	N/A	C1080T	N/A	350	
400					400	
450			450			
500			N/A	N/A	500	
600					600	
700					700	
800	800					

SIZE	ROTEX 42	ROTEX 55	ROTEX 65	ROTEX 75	ROTEX 90	C1060T	C1080T
Maximum Bore Diameter Inches (mm)	2.125 (52)	2.813 (70)	3.000 (75)	3.625 (92)	4.250 (105)	2.375 (60)	3.375 (85)

NOTES:

- 1) ROTEX is a registered trademark of KTR Corporation.
- 2) C1060T AND C1080T sizes are registered trademarks of Clarke Corporation.
- 3) Coupling selections are for UL-Listed couplings only.
- 4) Couplings cannot be used with diesel engines.
- 5) N/A indicates no UL-listed coupling is available for this horsepower-speed combination.